

**KF Titration and Potentiometer**
**KF Titration and Potentiometer**
**Auto Karl Fisher Titrator CL-510**

Min. delectability of Moisture	0.5 mg
Accuracy	0.25 mg
Burette capacity	10 ml
Burette resolution	0.05 ml
Stirrer	Variable speed
End point	Electronically timed with audible buzzer and a bar LED display
Power	230V, 50 Hz


**Universal Auto Titrator CL-520**

Measurement and Titration range	
PH Range	0 - 14 PH
Milli volt range	0 to ±1999 mV, 0 to ± 1400 mV (for titration)
Resolution	0.01 PH and 1 mV
Repeatability	± 0.05 PH ± 1 digit for PH ± 2 mV ± digit for mV
Temp (manual)	0 to 100 °C
Read out	3 ½ digit
Reproducibility	0.05 ml of Titrant
Stirrer	Variable speed
End point indication	Audio alarm and LED Display
Power	230V, 50 Hz


**Auto Karl Fisher Titrator CL-525**

MV Range	0 to 1999 MV
Resolution	1 MV
Repeatability	1 MV
Display Point	3½ Digital LED with Auto Polarity & Decimal Point
Power	230V 10%, 50 Hz


**Digital Automatic Karl Fisher Titrator CL-530**

Moisture Range	10 ppm to 100% accuracy
Display Readability	0.01 ML to 99.99 ML
Stirrer	Variable speed
Power	230V, 50 Hz


**CROMTECH INDIA**

1st Floor Begum Niwas, Opp Mercantile, Bank Soceity Colony, 5th Natwar Nagar Road, Jogeshwari (East), Mumbai 400 060.

Maharashtra - India.

Mobile: +91 98693 82134 / 81088 13320

Telefax: +91 22 2838 6028

 Email: [cromamumbai@mail.com](mailto:cromamumbai@mail.com) / [cromtechindia@mail.com](mailto:cromtechindia@mail.com) / [info@cromtechindia.com](mailto:info@cromtechindia.com) / [sales@cromtechindia.com](mailto:sales@cromtechindia.com)

 Website: [www.cromtechindia.com](http://www.cromtechindia.com)