

Turbidity Meter CL 810 /880


| Digital Turbidity Meter CL-810 | |
|---------------------------------------|--|
| Range | 0 - 1 NTU, 0 - 10 NTU, 0 - 100 NTU, 0 - 1000 NTU |
| Accuracy | ± 3% of FS in 0.1 & 0 - 1000 NTU Range (upto 500) [due to nature of samples, readings may not be linear above 500] |
| Reproducibility | within ± 3% of FS |
| Detector | Photo cell |
| Display | Digital Panel Meter |

| Micro Controller Based Digital Turbidity Meter CL-880 | |
|--|---|
| Range | 0 - 1 NTU, 0 - 10 NTU, 0 - 100 NTU, 0 - 1000 NTU |
| Accuracy | ± 2% of FS in 0.1 & 0 - 1000 NTU Range (upto 500) [due to nature of samples, readings may not be linear above 500] ± 1% of FS in 0 - 10 and 0 - 100 NTU range |
| Reproducibility | within ± 3% of FS |
| Detector | Round Photo cell |
| Display | 20 x 4 Digital LCD |
| Calibration | with Formazine Standard Solution |
| Power Supply | 230V ± 10%, 50 Hz, 30W |

CROMTECH INDIA

1st Floor Begum Niwas, Opp Mercantile, Bank Society Colony, 5th Natwar Nagar Road, Jogeshwari (East), Mumbai 400 060.
 Maharashtra - India.

Mobile: +91 98693 82134 / 81088 13320

Telefax: +91 22 2838 6028

Email: cromamumbai@mail.com / cromtechindia@mail.com / info@cromtechindia.com / sales@cromtechindia.com

Website: www.cromtechindia.com